

2009 STATISTICS – REGULATIONS CITED ON INSPECTION REPORTS ISSUED TO EMPLOYERS IN THE LOCAL GOVERNMENT CLASSIFICATION UNIT

Regulation	Number of IR's	Narrative
OHS 4.8 (2) (a)	12	<p>4.8 Rated capacity</p> <p>(2) The rated capacity or rated load must be certified by a professional engineer if</p> <p>(a) the manufacturer's specification or other acceptable warranty cannot be produced,</p>
OHS 31.32	11	<p>31.32 Vehicle exhaust in firehalls</p> <p>Unless air monitoring shows that levels of vehicle exhaust gas components are below the exposure limits established under section 5.48, effective local venting for the exhaust gases must be provided in vehicle areas in firehalls.</p>
OHS 14.35 (1)	10	<p>14.35 Pre-use inspection</p> <p>(1) Before an operator uses a crane or hoist, the operator must ensure that (a) the crane or hoist was inspected for that work shift, and (b) the control and safety devices were tested for that work shift.</p>
WCA 115 (2) (e)	10	<p>115 (2) Without limiting subsection (1), an employer must...</p> <p>(e) provide to the employer's workers the information, instruction, training and supervision necessary to ensure the health and safety of those workers in carrying out their work and to ensure the health and safety of other workers at the workplace</p>
OHS 18.3	9	<p>18.3 Standards for traffic control</p> <p>Traffic control equipment, arrangements and procedures must meet the requirements of the latest edition of the <i>Traffic Control Manual for Work on Roadways</i> (the "<i>Traffic Control Manual</i>") issued by the Ministry of Transportation, unless otherwise specified by this Regulation.</p>
OHS 4.55 (a)	8	<p>4.55 Guardrail locations</p> <p>An area accessible to workers must have guards or guardrails installed in any of the following circumstances:</p> <p>(a) if a raised floor, open-sided floor, mezzanine, gallery, balcony, work platform, ramp, walkway, or runway is 122 cm (4 ft) or more above the adjacent floor or grade level</p>

Regulation	Number of IR's	Narrative
WCB 187 (2)	7	<p>General authority to make orders</p> <p>187 (1) The Board may make orders for the carrying out of any matter or thing regulated, controlled or required by this Part or the regulations, and may require that the order be carried out immediately or within the time specified in the order.</p> <p>(2) Without limiting subsection (1), the authority under that subsection includes authority to make orders...</p>
OHS 3.5	6	<p>3.5 General requirement</p> <p>Every employer must ensure that regular inspections are made of all workplaces, including buildings, structures, grounds, excavations, tools, equipment, machinery and work methods and practices, at intervals that will prevent the development of unsafe working conditions.</p>
OHS 5.38 (2)	6	<p>38 Handling and securing cylinders</p> <p>(2) A compressed gas cylinder must be secured to prevent falling or rolling during storage, transportation and use, and where practicable, must be kept in the upright position.</p>
OHS 9.5	6	<p>9.5 Confined space entry program</p> <p>Before a worker is required or permitted to enter a confined space, the employer must prepare and implement a written confined space entry program</p>
OHS 14.12(2)	6	<p>14.12 Manual and instructions</p> <p>(2) A crane or hoist must not be used unless the following is reasonably accessible to the equipment operator and other persons inspecting or maintaining the equipment at the workplace where the crane or hoist is to be used:</p> <p>(a) the manufacturer's manual for the crane or hoist;</p> <p>(b) if the manufacturer's manual is not available, an engineer's instructions for the crane or hoist.</p>
OHS 14.71 (1)	6	<p>14.71 Annual inspection</p> <p>(1) A mobile crane or boom truck must be inspected at least once every 12 months in accordance with good engineering practice...</p>