

**THE CORPORATION OF DELTA
SAFE WORK PROCEDURE – 3M SUPER 77 SPRAY ADHESIVE**

LOCATION: Municipal Hall

DATE PREPARED: October 27, 2003

LAST REVISION:

PERSONAL PROTECTIVE EQUIPMENT REQUIRED FOR THE JOB: Side-vented goggles or safety glasses with side shields; gloves made of nitrile rubber, polyethylene/ethylene vinyl alcohol, polyvinyl alcohol, Teflon or Viton, half-mask organic vapour respirator if used indoors (Fit test required)

JOB STEP	HAZARDS	PRECAUTIONS
Using spray adhesive	This product can cause eye irritation, central nervous system depression, mild skin irritation.	Use only outdoors or in a specially ventilated room. Wear appropriate personal protective equipment including: Goggles or safety glasses Gloves Half mask respirator fitted with organic vapour cartridge if used indoors
Use of respirator	Half mask respirator can only be used in areas with sufficient oxygen to sustain life. An improperly fitted respirator will not provide adequate protection	A fit test is required before using a respirator.
Use of product and storage of containers	The aerosol container contains flammable gas under pressure; extremely flammable liquid and vapour.	Do not use near heat, sparks, open flame, or other sources of ignition. Store at temperatures below 120 degrees F (49 degrees C).