

**THE CORPORATION OF DELTA
SAFE WORK PROCEDURE – 3M SUPER 77 SPRAY ADHESIVE**

LOCATION: Municipal Hall

DATE PREPARED: October 27, 2003

LAST REVISION:

PERSONAL PROTECTIVE EQUIPMENT REQUIRED FOR THE JOB: Side-vented goggles or safety glasses with side shields; gloves made of nitrile rubber, polyethylene/ethylene vinyl alcohol, polyvinyl alcohol, Teflon or Viton, half-mask organic vapour respirator if used indoors (Fit test required)

| JOB STEP | HAZARDS | PRECAUTIONS |
|---|--|---|
| Using spray adhesive | This product can cause eye irritation, central nervous system depression, mild skin irritation. | Use only outdoors or in a specially ventilated room. Wear appropriate personal protective equipment including: Goggles or safety glasses Gloves Half mask respirator fitted with organic vapour cartridge if used indoors |
| Use of respirator | Half mask respirator can only be used in areas with sufficient oxygen to sustain life. An improperly fitted respirator will not provide adequate protection | A fit test is required before using a respirator. |
| Use of product and storage of containers | The aerosol container contains flammable gas under pressure; extremely flammable liquid and vapour. | Do not use near heat, sparks, open flame, or other sources of ignition. Store at temperatures below 120 degrees F (49 degrees C). |